



Quality is in our nature

Automatic transmission fluids - CVT

Eurol CVT 1304

Full synthetic automatic transmission fluid for CVT's

Descripción

Eurol CVT 1304 is a full synthetic transmission oil for the lubrication of modern Continue Variable Transmissions (CVT's).

Eurol CVT 1304 can be applied in all metal-belt, which are mentioned under Performance Level.

Eurol CVT 1304 offers optimal protection of the CVT under every condition and prevents wear at the metal-metal contact points on the belts and pulleys.

Eurol CVT 1304 protects the metal parts against wear and corrosion as well as inconvenient vibrations. Because of the special additives this oil has a durable quality, even under ongoing pressure.

Eurol CVT 1304 is formulated to prevent air entry and foam building in order to guarantee optimum lubrications.

Specifications

<u>Recommended for use</u>	Dia Queen CVTF J4	Subaru Lineartronic CVTF
BMW 83 22 0 136 376	Elf Matic CVT	Suzuki CVT Green 1
BMW 83 22 0 429 154	EZL-799	Suzuki CVTF Green 2
Chrysler CVTF+4	Ford CVT23	Suzuki NS-2
CVT EZL 799 A	Honda HCF-2	Toyota CVT FE
DAIHATSU AMIX CVT FLUID	Honda HMMF	Toyota CVT TC
DC	MB 236.20	VW G 052 180
Daihatsu CVTF DFE	Mopar CVTF +4	VW G 052 516
Daihatsu/Suzuki TC	Nissan NS-3	Ford WSS-M2C928-A
DEX-CVT	Nissan NS-2	
Dia Queen CVTF J1	Nissan NS-1	

Propiedades físicas

Color	Ambarino	
Densidad a 20°C	0.849 kg/l	ASTM D 1298
Viscosidad, cinemático a 40°C	33.6 cSt	ASTM D 445
Viscosidad, cinemático a 100°C	7.2 cSt	ASTM D 445
Índice de viscosidad	186	ASTM D 2270
Punto de inflamación	170 °C	ASTM D 93
Punto de fluidez	-42 °C	ASTM D 97

Available in 1L - 20L - 60L - 200L - 210L

E113663

Versión 1.0, 25-03-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Países Bajos, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com