



Quality is in our nature

Coolants & screenwash - Cooling fluids

Eurol Coolant XL -36°C

Universal long-life coolant, miscible with the most commercial coolants

Descripción

Eurol Coolant XL -36 is a universal long-life coolant, based on mono-ethylene-glycol and organic corrosion inhibitors (silicate-free). This special technology can be mixed with coolants of other brands without the risk of sludge build-up and decreasing cooling capabilities.

Eurol Coolant XL -36 can be mixed with most mono-ethylene-glycol based commercial coolants, a.o. Volkswagen and Renault.

Eurol Coolant XL -36 prevents from scale formation and offers an excellent protection against cavitation. Moreover, it protects metal parts in the cooling system against corrosion.

Eurol Coolant XL -36 is nitrite, amine, borate, phosphate, nitrate and silicate-free and in this way, contributes to a cleaner environment.

Eurol Coolant XL -36 is completely safe for rubber, plastics, metals and aluminium or its alloys.

Eurol Coolant XL -36 is a modern coolant for water-cooled combustion engines and protects the system from freezing up to -36 °C.

Eurol Coolant XL -36 is to be used undiluted, so never top-up with water. Life-time of the product is 5 years or 650.000 km for trucks or 250.000 km for passenger cars, depending on which situation occurs first.

Always follow the instructions of the manufacturer regarding application of the right coolant.

Specifications

<u>Performance level</u>	Renault Type D	STJLR 651.5003
VW TL-774 F (G12+)	MTU MTL 5048	
VW TL-774 D (G12)	Liebherr MD1-36-130	
BS 6580	Komatsu 07.892	
ASTM D4985	John Deere JDM H5	
ASTM D4656	JASO M325	
ASTM D3306	GM 6277M	
AFNOR NFR 15-601	Ford WSS-M97B44-D	
MB 326.3	DAF 74002	
MAN 324 Typ SNF	Case New Holland	
SAE J1034	MAT3624	

Propiedades físicas

Color	Amarillo	
Densidad a 20°C	1.069 kg/l	ASTM D 1298
Punto de inflamación	111 °C	ASTM D 93
Resistencia a las heladas	-36 °C	ASTM D 1177

Available in 1L - 5L - 20L - 60L - 200L - 210L - IBC - BULK

E504140

Versión 1.1, 24-11-2017

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Países Bajos, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com