



Quality is in our nature

Technical fluids - Brakefluids

# Eurol Brake Fluid DOT 5.1

Brake fluid for hydraulic drum brake - and disc brake systems

## Descripción

Eurol Brake Fluid DOT 5.1 is recommended for ABS and ASR brake systems. Especially the low viscosity of this product compared to DOT 3 and DOT 4 brake fluids stand out very well in these systems.

Eurol DOT 5.1 will not affect sealing cups, brake fluid pipes or seal rings.

Eurol DOT 5.1 has a high 'wet boiling point' by which the risk of vapour lock is strongly reduced. This is important when asbestos-free brake lining is used, which is connected with the evolution of higher heat. N.B.: For safety reasons, brake fluid has to be changed regularly, according to OEM instructions.

Eurol DOT 5.1 can be mixed with other synthetic brake fluids, meeting FMVSS 116 DOT 3, DOT 4 and DOT 5.1 specifications.

"Attention:

Brake Fluid will attack car paints. When spilled, rinse off with water immediately. Store in well closed packaging and avoid contamination with water or lubricants."

## Specifications

Performance level

FMVSS 116 DOT 5.1

ISO 4925 class 5.1

SAE J1703

## Propiedades físicas

Color	Amarillo	
Densidad a 20°C	1.065 kg/l	ASTM D 1298
Viscosidad, cinemático a 40°C	7 cSt	ASTM D 445
Viscosidad, cinemático a 100°C	2.1 cSt	ASTM D 445
Punto de inflamación	100 °C	ASTM D 93
Punto de fluidez	-36 °C	ASTM D 97
Dry Boiling Point	>260 °C	SAE J1703
Wet Boiling Point	>180 °C	SAE J1703

Available in 250ML - 1L - 5L - 60L

E801500

Versión 1.1, 12-05-2017

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Países Bajos, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com